

# 规格書

## SPECIFICATION

Customer : \_\_\_\_\_

Part Name: \_\_\_\_\_ **E-CAP** \_\_\_\_\_

SPEC : \_\_\_\_\_ **SP Series** \_\_\_\_\_


Part NO. : \_\_\_\_\_ **ALL** \_\_\_\_\_

Date : \_\_\_\_\_ **2017-11-22** \_\_\_\_\_

CUSTOMER SIGN		

TOPAZCON	
DRAWING	RATIFY
黃峰	陳慶

## SP Series




- Miniaturized, Low ESR and low impedance.
- Suitable for use in high ripple current capability.
- Load life 4,000 hours at 105 °C

### SPECIFICATIONS

Item	Performance Characteristics					
Category	-40 ~ +105 °C					
Temperature Range	10 ~ 100Vdc					
Working Voltage Range	68 ~ 1,800 μF					
Capacitance Range	± 20% (at 20 °C and 120Hz)					
Capacitance Tolerance	Rated Voltage (V)	10	16	25	35	100
Dissipation Factor (tanδ)	Tanδ(Max)	0.19	0.16	0.14	0.12	0.08
	The above values should be increased by 0.02 for every additional 1000μF (at 20 °C , 120Hz)					
Leakage Current	I=0.01CV or 3μA whichever is greater I : Leakage current (μA) C : Rated capacitance (μF) V : Rated voltage (V) (at 20 °C , 2minutes)					
Endurance	The following requirements shall be satisfied when the capacitor are restored to 20 °C after the rated voltage applied for 4,000 hours at 105 °C .					
	Capacitance change	≅ ± 25% of the initial value				
	Dissipation factor(tanδ)	≅ 200% of the specified value				
	Leakage current	≅ specified value				
Shelf Life	The following requirements shall be satisfied when the capacitor are restored to 20 °C after exposing them for 500 hours at 105 °C without voltage applied.					
	Capacitance change	≅ ± 25% of the initial value				
	Dissipation factor(tanδ)	≅ 200% of the specified value				
	Leakage current	≅ 200% of the specified value				

### DIMENSIONS[MM]



Φ D	12.5 × 12
Φ D	Φ D+0.5Max
Φ d	0.6
F	5.0
a	L + 1.0 Max

### RATED RIPPLE CURRENT MULTIPLIERS

Frequency Multipliers

Vdc	Cap.(μF)	Frequency (Hz)			
		120	1K	10K	100K
10 ~ 100	≥ 68	0.30	0.65	0.85	1.00
	82 ~ 220	0.50	0.70	0.90	1.00
	330 ~ 820	0.60	0.75	0.95	1.00
	1000 ~ 1800	0.70	0.80	0.98	1.00


## SP Series

● Case size & Permissible rated ripple current:

Nominal capacitance (uF)	10V		16V		25V	
	Case size DΦ×L (mm)	Max. Rated ripple current @105℃ 100kHz (mA rms)	Case size DΦ×L (mm)	Max. Rated ripple current @105℃ 100kHz (mA rms)	Case size DΦ×L (mm)	Max. Rated ripple current @105℃ 100kHz (mA rms)
560					12.5×12	1150
680					12.5×12	1200
1000			12.5×12	1300		
1200			12.5×12	1400		
1500	12.5×12	1260				
1800	12.5×12	1300				

Nominal capacitance (uF)	35V		100V	
	Case size DΦ×L (mm)	Max. Rated ripple current @105℃ 100kHz (mA rms)	Case size DΦ×L (mm)	Max. Rated ripple current @105℃ 100kHz (mA rms)
68			12.5×12	350
82			12.5×12	420
390	12.5×12	1050		
470	12.5×12	1100		

## Part Number System



### ① Series code

Series name	Code	
	1	2
SM	S	M
SS	S	S
SH	S	H
SP	S	P
NP	N	P
LL	L	L
RD	R	D
RE	R	E
RT	R	T
RF	R	F
RG	R	G
RJ	R	J
RR	R	R
LF	L	F
LJ	L	J
LR	L	R
LG	L	G

### ② Voltage code

WV (V <sub>dc</sub> )	Code	
	3	4
4	0	G
6.3	0	J
10	1	A
16	1	C
25	1	E
35	1	V
50	1	H
63	1	J
80	1	K
100	2	A
160	2	C
200	2	D
250	2	E
350	2	V
400	2	G
450	2	W
500	2	H

### ③ Capacitance code

Cap (uF)	Code		
	5	6	7
0.1	R	1	0
0.22	R	2	2
0.33	R	3	3
0.47	R	4	7
1	1	R	0
2.2	2	R	2
3.3	3	R	3
4.7	4	R	7
6.8	6	R	8
10	1	0	0
22	2	2	0
33	3	3	0
47	4	7	0
100	1	0	1
220	2	2	1
330	3	3	1
470	4	7	1
560	5	6	1
1000	1	0	2
1500	1	5	2
2200	2	2	2
3300	3	3	2
4700	4	7	2
6800	6	8	2
10000	1	0	3
15000	1	5	3

### ④ Capacitance tolerance code

Tol. (%)	Code
	8
-5 ~ +5	J
-10 ~ +10	K
-20 ~ +20	M

### ⑤ Size code

ΦD × L (mm)	Code			
	9	10	11	12
3 × 5	0	3	0	5
4 × 5	0	4	0	5
5 × 5	0	5	0	5
6.3 × 5	0	6	0	5
4 × 7	0	4	0	7
5 × 7	0	5	0	7
6.3 × 7	0	6	0	7
8 × 7	0	8	0	7
5 × 11	0	5	1	1
6.3 × 11	0	6	1	1
8 × 12	0	8	1	2
8 × 16	0	8	1	6
10 × 12	1	0	1	2
10 × 16	1	0	1	6
8 × 20	0	8	2	0
10 × 20	1	0	2	0
13 × 20	1	3	2	0
13 × 25	1	3	2	5
16 × 25	1	6	2	5
16 × 32	1	6	3	2
16 × 36	1	6	3	6
18 × 32	1	8	3	2
18 × 36	1	8	3	6
18 × 40	1	8	4	0

### ⑦ Sleeve/Marking code

Sleeve/Marking	Code 14
PET	T
Black	B
Yellow	Y
Ink Green	I
Pea Green	P
Orange	O

### ⑥ Terminal code

Specification	Code 13
Bulk packing	0
Φ4-8Taping	T1
	T2
	T2
Φ10-18Taping	T3
	T3
Lead Cut	F
	C
	R
	L
	M
	S
	B
	K
	K

Lead Forming

Taping Specifications

Fig.1 Code:T1




Fig.2 Code:T2




Fig.3 Code:T2





Fig.4 Code:T3




**Specification Fig.1 & Fig.2 & Fig.3**

Items	Symbol	CASE SIZE										Tolerance					
		4 × 5 4 × 7		5 × 5 5 × 7		5 × 11		6.3 × 5		6.3 × 7 6.3 × 9			6.3 × 11 6.3 × 12		8 × 5/7 8 × 9/11 8 × 11.5 8 × 12		8 × 16 8 × 20
Pin Code		T <sub>1</sub>	T <sub>2</sub>	T <sub>1</sub>	T <sub>2</sub>	T <sub>1</sub>		T <sub>2</sub>	T <sub>2</sub>	T <sub>2</sub>	T <sub>2</sub>	T <sub>2</sub>	T <sub>2</sub>	T <sub>2</sub>			
Lead wire diameter	φd	0.45		0.45		0.5		0.45	0.5	0.5	0.5	0.45/0.5		0.6	0.6	± 0.05	
Pitch of body	P	12.7		12.7		12.7		12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	± 1.0	
Feed hole pitch	PO	12.7		12.7		12.7		12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	± 0.2	
Hole center to lead distance	P1	5.1	5.6	5.1	5.35	5.1	5.35	5.1	5.1	5.1	5.1	4.6	4.6	3.85	± 0.7		
Feed hole center to body center distance	P2	6.35		6.35		6.35		6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	± 1.0	
Lead to lead distance	F	2.5	1.5	2.5	2.0	2.5	2.0	2.5	2.5	2.5	2.5	3.5	3.5	5.0	± 0.5		
Height of body from tape center	H	18.5		18.5		18.5		18.5	18.5	18.5	18.5	18.5	18.5	18.5	18.5	± 0.75	
Base tape width	W	18.0		18.0		18.0		18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	± 0.5	
Adhesive tape width	WO	11.0		11.0		11.0		11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	min	
Hole positron	W1	9.0		9.0		9.0		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	+0.75 -0.5	
Hole down tape position	W2	3.0		3.0		3.0		3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	max	

**Specification Fig.4**

Items	Symbol	CASE SIZE									Tolerance						
		4 × 5 4 × 7		5 × 5		5 × 7		5 × 11		6.3 × 5		6.3 × 7 6.3 × 9		6.3 × 11 6.3 × 12		8 × 5/7 8 × 9/11 8 × 11.5/12	
Pin Code		T <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>	T <sub>3</sub>		
Lead wire diameter	φd	0.45		0.45		0.45		0.5	0.45	0.5	0.5	0.5	0.45/0.5		0.6	± 0.05	
Pitch of body	P	12.7		12.7		12.7		12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	± 1.0	
Feed hole pitch	PO	12.7		12.7		12.7		12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	± 0.2	
Hole center to lead distance	P1	3.85		3.85		3.85		3.85	3.85	3.85	3.85	3.85	3.85	3.85	3.85	± 0.7	
Feed hole center to body center distance	P2	6.35		6.35		6.35		6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	± 1.0	
Lead to lead distance	F	1.5		2.0		2.0		2.0	2.5	2.5	2.5	3.5	3.5	3.5	± 0.5		
Lead to lead distance	F1	5.0		5.0		5.0		5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	+0.8 -0.2	
Height of body from tape center	H	18.5		18.5		18.5		18.5	18.5	18.5	18.5	18.5	18.5	18.5	18.5	± 0.75	
Lead wire clinch height	HO	16.0		16.0		16.0		16.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0	± 0.5	
Base tape width	W	18.0		18.0		18.0		18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	± 0.5	
Adhesive tape width	WO	11.0		11.0		11.0		11.0	11.0	11.0	11.0	11.0	11.0	11.0	11.0	min	
Hole position	W1	9.0		9.0		9.0		9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	+0.75 -0.5	
Hole down tape position	W2	3.0		3.0		3.0		3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	max	

● Lead Forming & Cut:




● LEAD SPACING & RECOMMENDED PCB DIMENSIONS

(mm)


Dimension	φD	φd	p	PC Board		Lead Configuration
				Hole diameter	Thickness	
5	5	0.5	5.0	0.8	1.6	F C S
6.3	6.3	0.5	5.0	0.8		
8	8	0.5/0.6	5.0	1.0		
10	10	0.6	5.0	1.0	1.6	C M R L
12.5	12.5	0.6	5.0	1.0		
16	16	0.8	7.5	1.2		
18	18	0.8	7.5	1.2		
20	20	0.8	7.5	1.2		
22	22	0.8	10.0	1.2		

● Lead configuration: B



∅D	L1	L2	K	A	L	
5	17.5-19.5	2.6	1.9	10.0-15.0	3.0-5.0	
6.3	17.5-19.5	2.6	1.9	10.0-16.0		
8	12.0-14.0	2.5	1.3	10.0-20.0		
8	13.5-15.5	2.5	1.5			
8	13.0-15.0	3.0	1.5			
8	19.5-21.5	3.0	1.5			
8	21.0-23.0	3.0	1.5			
10	7.5-9.5	2.5	1.7	10.0-25.0		
10	17.0-19.0	2.5	1.7			
10	10.5-12.5	2.5	1.5			
10	10.0-12.0	3.0	1.5			
10	13.0-15.0	3.0	1.5			
10	18.0-20.0	3.0	1.5			
10	21.0-23.0	3.0	1.5			
	± 1.0	± 0.5	0.3	± 1.0		± 1.0

● Lead configuration: K



∅D	C	B	E	F	G	A	H
8	13.5-15.5	3	1.2	1.8	0.8	10-20	3.0-5.0
10	18.5-20.5	3	1.2	1.8	1	10-25	
10	19.0-21.0	3	1.5	1.4	0.5		
	± 1.0	± 0.5	± 0.3	± 0.3	± 0.3	± 1.0	± 1.0